

WCS Series

WCS1160




11.6" Touch All-in-One System PPC with Intel Processor



PCAP



Fanless



True Flat



VESA



Low Power



- Slim Metal Housing & Light Weight Design
- 16:9 Full HD 1920 x 1080 Resolution IPS TFT LCD Panel
- True Flat with 10 Point Capacitive Multi-touch Type
- Rich I/O Ports Provide Excellent Peripheral Connectivity
- Passive Cooling (fanless)
- 1 Pogo Pin Landscape for Optional Accessories: MSR Module, 2D Barcode Scanner Module, NFC Module, 7" Second Display



Vending Machine



Fitness Club



Restaurant Ordering



Gaming Lottery



Interactive Kiosk

Specification

WCS1160

Display

Display Type	11.6" IPS TFT LCD
Resolution	1920 x 1080 pixel
Brightness	350 nits
Contrast Ratio	1000
Viewing Angle	Horizontal 160° / Vertical 160°
Viewing Area	256.9mm x 144.5mm
Touch Screen Type	Projected Capacitive (10 Points)

Main System

Processor	Intel® Celeron® Processor N3160 (optional: Intel® Pentium® Processor N3710)
Graphics	Intel HD Graphics Gen8
Memory	DDR3L 1600 4GB Standard
Storage	64GB M.2 2242 SSD TLC
Audio	Realtek ALC282
System I/O	2 x USB 3.0 3 x USB 2.0 1 x DC in 1 x Add-on Module Slot 1 x mini HDMI
Ethernet	1 x RJ45 10/100/1000 Mbps connector
Wireless Communication	Wi-Fi IEEE802.11b/g/n module (optional) Bluetooth 4.0 (optional)
OS Support	Windows Embedded POSReady 7 (64bit) Windows Embedded Industry 8.1 (64bit) Windows 10 IoT (64bit)

Physical

Housing	Metal
System Indicator	1 x Power LED
Physical Button	1 x Power button
Speaker	2 x 2W
Adapter Power	Input: 100-240Vac, 1.5A, 50-60Hz Output: 12Vdc, 3.33A
Energy Efficiency Rating	DOE 2013 Level VI
RoHS	Yes
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Humidity	Storage: 10% ~ 70% (Non-condensing)
Dimensions	295.8mm x 189.6mm x 34.9mm
Weight	1.31kg
Mounting	VESA 75x75
Certification	CE, FCC
Optional Accessory	MSR module, 2D barcode scanner module, NFC module, 7" second display, Easy stand, IO stand
Warranty	2 years

Dimensions

Unit : mm

